REBTRADE INTERNATIONAL CORPORATION

REBEPOXY

Structural Bonding Epoxy

PRODUCT DESCRIPTION

Solvent free, non-pigmented, two component preparation of liquid epoxy resin base with formulated amine hardeners.

REBEPOXY, when fully hardened, is water and weather-proof; resistant to sea water, lyes, diluted acids, saline solutions, greases, fuels and mineral oil.

USES & APPLICATIONS

REBEPOXY is particularly suitable for strong joining of concrete sections, of new concrete onto old concrete, and iron to concrete.

INSTALLATION PROCEDURE

Cement bound surfaces must be dry, firm, offer good traction, and be free from grout, dust and dirt particles, and additionally be free of oil, grease and other impurities which can adversely affect uniform adhesion. If considered necessary, the surface should be sand blasted or grinded.

Iron and steel must be free of rust, scale, oil, dust, grease and other impurities. The best surface preparation is sand blasting.

For structural bonding of fresh concrete and old concrete, sandblast or grind the top surface, if necessary. Apply REBEPOXY to the surface to be joined.

PACKAGING & COVERAGE

Minimum consumption is approximately 8-10 sqm per gal.kit.

Packaging comes in 1 gallon which is equivalent to 4 liters (Resin and Hardener are supplied in correct mix). Mix ratio is 1:1.

MAIN OFFICE: Unit 2B Magara Townhomes. Sierra Madre cor. Esteban Sts. Mandaluyong City, Philippines **TEL NOS.:** 531.4654 to 55 **FAX NO.:** (632) 531.2768